



HR3280-HC
Marlin
healthcare
handheld scanner

FEATURES

Megapixel camera.

The HR3280-HC Marlin is a barcode scanning powerhouse. No matter what type of barcode is presented, the megapixel camera allows users to scan 1D and 2D barcodes, including very small and high density ones, with impressive speed and ease.

Durable construction.

Users in retail setting will enjoy the strong exterior and drop resistance up to 1.5m. With an IP42 rating, the device is protected against water and dust.

Superior ergonomics.

Blending ergonomic and aesthetics in its design, the HR3280-HC Marlin not only ensures operator comfort and productivity for intensive handheld scanning, but also meets the aesthetic needs of the healthcare environments.

Disinfectant-ready enclosure.

The HR3280-HC Marlin housing and stand are created with nSHIELD, an antimicrobial surface that is built to resist harsh cleaning agents commonly used in healthcare environments and minimize the spread of infections.

Humanized illumination.

The HR3280-HC Marlin has white and red LED according to different workplaces. Not only relieving the visual fatigue but also improving working efficiency.

Foldable smart stand available.

A foldable smart stand comes in a SET with the scanner.



HR3280-HC Marlin with stand.

Application Scenarios

Healthcare • labs • physical exam rooms • assets counting and more.

HR3280-HC Marlin

healthcare handheld scanner

newland-id.com

Performance	Image Sensor	1280x800 CMOS		
	Illumination	White LED & Red LED		
	Aiming	Green LED		
	Symbologies	2D	PDF417, Micro PDF417, QR Code, Micro QR Code, Aztec, Data Matrix, Chinese Sensible Code, Maxicode, GM Code, Code One.	
		1D	EAN-8, EAN-13, UPC-E, UPC-A, Code128, Coupon, UCC/EAN128, CodaBar, I2Of5, Febraban, ITF14, ITF6, Matrix 25, Code39, Code93, ISSN, ISBN, Industrial 25, Standard 25, China Post 25, Plessey, Code 11, MSI Plessey, UCC/EAN Composite, GS1 Databar, Code 49, COOP 25, Code 16K, AIM 128, ISBT 128.	
		Postal	USPS Postnet, USPS Intelligent Mail, Royal Mail, USPS Planet, KIX Post, Australian Postal, Japan Post.	
		OCR	Passport OCR.	
	Resolution*	≥3mil		
	Typical Depth of Field*	EAN-13	45mm-510mm (13mil)	
		Code 39	75mm-220mm (5mil)	
		PDF 417	70mm-215mm (6.7mil)	
		Data Matrix	50mm-220mm (10mil)	
		QR Code	20mm-330mm (15mil)	
	Scan Angle**	Pitch	±55°	
		Skew	±55°	
Tilt		360°		
Field of View	Horizontal 39°, Vertical 24°			
Min. Symbol Contrast	25%			
Physical	Interfaces	RS-232, USB		
	Dimensions (LxWxH)	159.0x113.5x73.3mm		
	Weight	162g		
	Notification	Beep, LED indicator		
	Rated Power Consumption	1289.6mW (typical)		
	Current@5VDC	Operating	241.2mA(typical), 260.5mA(max.)	
		Standby	71.3mA	
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)		
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)		
	Humidity	5% ~ 95% (non-condensing)		
	ESD	±15KV (air discharge); ±8 KV (contact discharge)		
	Drop	1.5m		
	Sealing	IP42		
	Approved Cleaners	Disinfectant Ready. Refer to the user guide for the list of approved cleaners.		
Certifications	FCC Part15 Class B, CE EMC Class B, RoHS			

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp
2D: QR Code; 1D Bytes; Resolution=15mil; PCS=0.8.

Specification are subject to change without notice

Version: V1.0

Contact Dakota to find out more:

+44 (0) 161 776 4009
nhs@dakotais.co.uk
dakotais.co.uk

