

Tablets





backside of the SD100

SD100MD Orion

Provide superior (health) care with this antibacterial coated 10" Android tablet.

Healthcare



About the product

- Supports 1D and 2D barcodes
- Built on Android 8.1
- 10.0 inch (1920x1200) 5-point capacitive touch screen
- Octa-core 2.0GHz CPU
- 4GB RAM and 64GB ROM memory

- Offers: WIFI 802.11 a/b/g/n (2.4GHz & 5GHz),


Bluetooth 4.1, GPS, Camera, NFC, GSM, WCDMA

• Designed and manufactured according to the

• Magnetic support wristband for ease of use

EC60601-01 standard





Technical specifications

| MODEL | SD100MD |
|-----------------------|--|
| CPU | Octa-core 2.0GHz |
| OS | Android 8.1 |
| RAM | 4GB |
| ROM | 64GB |
| Camera | Rear 13MP AF, high brightness LED flash, front 5MP camera |
| Screen | 10" IPS highlight screen |
| Resolution | 1200x1920 |
| Touch screen | |
| | 5-point capacitive touch screen |
| Dimension | 254 x 176 x 17.4 mm |
| Weight (with battery) | 800g |
| Battery capacity | 9000mAh, typical working time not less than 10 hours |
| Charging | PE fast charge |
| Bluetooth | BT4.1 BLE |
| Wi-Fi | IEEE 802.11 a/b/g/n 2.4G 5G dual frequency |
| WLAN | FDD-LTE B1/B3/B5/B7/B8 |
| | TDD-LTE B38/B39/ B40/B41 |
| | TDSCDMA B34/B39 |
| | WCDMA B1/B2/B5/B8 |
| | GSM B2/B3/B5/B8 |
| | CDMA 1 x/CDMA2000 BC0/BC1 |
| GPS | GPS+BD+GLONASS |
| Audio | Front dual stereo speakers, Volume 90db±3db (test distance 10cm) |
| Sensor | Gsensor, Ambient light sensor, Proximity sensor, COMPASS |
| Interface | 2 Micro SIM card slots |
| | 1 SD card slot |
| | 3.5mm earphone jack |
| | USB Type-C |
| | 20 Pogo Pins contact |
| Keypad | 12 buttons |
| Notifications | Sound, vibration, LED |
| Operating temperature | -20°C to +55°C |
| Storage temperature | -30°C to +70°C |
| Humidity | 5%-95% |
| IP class | IP65 |
| Drop | 1 meter drop to cement floor |
| ESD | ± 15kV air discharge , ±8kV contact discharge |
| Certificates | CCC, CE |
| NFC | ISO14443A/B , ISO15693 , NFC Reading distance: 0~5cm |
| UHF RFID | ISO18000-6C |
| (optional) | Euro frequency (865MHz - 867MHz) |
| (орцона) | |
| | Antenna: 1.5dBi ceramic antenna Power: 5dBm~30dBm adjustable, 1dbm step |
| | |
| | Working range: Indoor >12m, Outdoor >6m |
| B | Inventory speed: >200 tags/sec |
| Barcode scanning | AZTEC, CODABAR, CODE11, CODE128, EAN128, CODE39, CODE49, CODE93, |
| | COMPOSITE, DATAMATRIX, EAN8, EAN13, INT25, MAXICODE, MICROPDF, PDF417, |

The product has been designed and manufactured according to the EC60601-01 standard.

POSTNET, OCR, QR, RSS, UPCA, UPCE, ISBT, BPO, CANPOST, AUSPOST, IATA25, CODABLOCK, JAPOST, PLANET, DUTCHPOST, MSI, TLC39, TRIOPTIC, CODE32, STRT25