



NLS-NQuire 1000

CUSTOMER INFORMATION TERMINAL

FEATURES

○ **Easy to Install and Use Anywhere**

Ideally suited for shelf mounting or on-counter usage in department stores, supermarkets, small grocery stores, drugs-cosmetic stores, tobacco kiosks and more.

○ **Snappy Reading Performance**

Armed with Newland's omnidirectional megapixel EM2037 engine (Resolution: 1280*800).

○ **Highly Customizable with a Broad Range of Features**

External SCR, Thermal Printer, Wi-Fi, Bluetooth embedded, Coms included, POE.

○ **Easily Build Applications**

The NQuire is built on Android 7.1, allowing for easy development of custom applications.



2D Barcode



1D Barcode



Android



USB



Ethernet



WiFi



Screen size

NLS-NQuire 1000

Performance

SOC	RK3368, Octa-core Cortex-A53; up to 1.5 GHz PowerVR G6110 GPU; up to 600MHZ
Operating System	Android 7.1
Memory	2GB DDR3, 8GB eMMC

Physical/Electrical

Dimensions (L×W×H)	252 × 184 × 33mm
Material	PC + ABS plastic
P-o-E (optional)	Power-over-Ethernet IEEE 802.3af
Weight	615 grams, main body only, without power adapter and metal bracket
Display	10.1" WXGA, 1280 × 800 TFT LCD display/10 points Capacitive Touch
VESA Mount Holes	Metal fitting mounting screw holes: 75 × 75 mm

Power Supply

Clock Battery	Lithium-ion non-rechargeable coin battery for RTC
DC Input	AC 100-240V, 50-60Hz, 2A Max, DC12V±5%
Power Consumption	1KHz audio playback etc. about 18W maximum, OFF: 0W
LED Indicator	1x LED/Power Supply ON: red, then turns green once kernel boot up Power Supply OFF: LED off

Environmental

Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	5% to 90% (non-condensing)
Sealing	IP54(front panel)

Barcode Scanning

2D Barcode	1D: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, GS1 Composite Code, Matrix 2 of 5, Code 11, Industrial 25, Standard 25, Plessey, MSI-Plessey, etc. 2D: PDF417, QR Code, Data Matrix, Chinese Sensible Code, Aztec Code, Maxicode, MicroPDF417*, etc.
CMOS (≥5mil)	

Connectivity

Wi-Fi	IEEE 802.11 b/g/n/ac (2.4G) , IEEE 802.11 a/b/g/n/ac (5G)
Bluetooth	BT 4.1
LAN	RJ45 Ethernet, 10/100/1000 Base T/POE (Power Over Ethernet)

Peripherals

Camera	Front: 5.0 MP camera
Audio	1x 3.5mm Headset + MIC jack, 2x Integrated speakers 8Ω/1.3W
Sensor	G Sensor
Other H/W	VESA mount: Metal-fitting mounting screw holes
Functional Keys	(Vol+ / Vol-) / (Up/Down) / Exit/Power switch

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

North America&Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlscan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd.,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw

NLS-NQuire 1000

I/O Ports

USB Port	1x USB 2.0 host, type A port, 1x Micro USB 2.0 port
SD Card Slot	SD Card (SDHC class 10 compatible) slot with cover
GPIO Port	1x GPIO port
Expansion Slot	2x POGO-PIN, USB 2.0/supports up to two modules working concurrently
DC-in	4mm DC-In jack, 12V/2A

Multimedia

Video	MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV
Audio	MP2, WMA, WAV, AAC, OGG, ASF
Picture	JPG, BMP, GIF

Accessory (Default)

Multi-plug AC/DC adapter with power cord

Certificates & Protection

CE, FCC, RoHS

Specifications are subject to change without notice.

Version: V1.4

Newland AIDC

Add: No.1 Rujiang West Rd,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

North America&Latin America

Add: 46559 Fremont Blvd,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlscan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw